NAME

epoll_ctl – control interface for an epoll descriptor

SYNOPSIS

#include <sys/epoll.h>

int epoll_ctl(int *epfd*, **int** *op*, **int** *fd*, **struct epoll_event ***event*);

DESCRIPTION

This system call performs control operations on the **epoll**(7) instance referred to by the file descriptor *epfd*. It requests that the operation *op* be performed for the target file descriptor, *fd*.

Valid values for the *op* argument are :

EPOLL_CTL_ADD
Register the target file descriptor *fd* on the **epoll** instance referred to by the file descriptor *epfd* and associate the event *event* with the internal file linked to *fd*.

EPOLL_CTL_MOD
Change the event *event* associated with the target file descriptor *fd*.

EPOLL_CTL_DEL
Remove (deregister) the target file descriptor *fd* from the **epoll** instance referred to by *epfd*. The *event* is ignored and can be NULL (but see BUGS below).

The *event* argument describes the object linked to the file descriptor *fd*. The *struct epoll_event* is defined as :

```
typedef union epoll_data {
   void        *ptr;
   int         fd;
   uint32_t    u32;
   uint64_t    u64;
} epoll_data_t;

struct epoll_event {
   uint32_t    events;     /* Epoll events */
   epoll_data_t data;       /* User data variable */
};
```

The *events* member is a bit set composed using the following available event types:

EPOLLIN
The associated file is available for **read**(2) operations.

EPOLLOUT
The associated file is available for **write**(2) operations.

EPOLLRDHUP (since Linux 2.6.17)
Stream socket peer closed connection, or shut down writing half of connection. (This flag is especially useful for writing simple code to detect peer shutdown when using Edge Triggered monitoring.)

EPOLLPRI
There is urgent data available for **read**(2) operations.

EPOLLERR
Error condition happened on the associated file descriptor. **epoll_wait**(2) will always wait for this event; it is not necessary to set it in *events*.

EPOLLHUP
Hang up happened on the associated file descriptor. **epoll_wait**(2) will always wait for this event; it is not necessary to set it in *events*.

EPOLLET
Sets the Edge Triggered behavior for the associated file descriptor. The default behavior for **epoll** is Level Triggered. See **epoll**(7) for more detailed information about Edge and Level Triggered event distribution architectures.

EPOLLONESHOT (since Linux 2.6.2)
Sets the one-shot behavior for the associated file descriptor. This means that after an event is pulled out with **epoll_wait**(2) the associated file descriptor is internally disabled and no other events will be reported by the **epoll** interface. The user must call **epoll_ctl**() with **EPOLL_CTL_MOD** to rearm the file descriptor with a new event mask.

RETURN VALUE

When successful, **epoll_ctl**() returns zero. When an error occurs, **epoll_ctl**() returns −1 and *errno* is set appropriately.

ERRORS

EBADF
epfd or *fd* is not a valid file descriptor.

EEXIST
op was **EPOLL_CTL_ADD**, and the supplied file descriptor *fd* is already registered with this epoll instance.

EINVAL
epfd is not an **epoll** file descriptor, or *fd* is the same as *epfd*, or the requested operation *op* is not supported by this interface.

ENOENT
op was **EPOLL_CTL_MOD** or **EPOLL_CTL_DEL**, and *fd* is not registered with this epoll instance.

ENOMEM
There was insufficient memory to handle the requested *op* control operation.

ENOSPC
The limit imposed by */proc/sys/fs/epoll/max_user_watches* was encountered while trying to register (**EPOLL_CTL_ADD**) a new file descriptor on an epoll instance. See **epoll**(7) for further details.

EPERM
The target file *fd* does not support **epoll**.

VERSIONS

epoll_ctl() was added to the kernel in version 2.6.

CONFORMING TO

epoll_ctl() is Linux-specific. Library support is provided in glibc starting with version 2.3.2.

NOTES

The **epoll** interface supports all file descriptors that support **poll**(2).

BUGS

In kernel versions before 2.6.9, the **EPOLL_CTL_DEL** operation required a non-NULL pointer in *event*, even though this argument is ignored. Since Linux 2.6.9, *event* can be specified as NULL when using **EPOLL_CTL_DEL**. Applications that need to be portable to kernels before 2.6.9 should specify a non-NULL pointer in *event*.

SEE ALSO

epoll_create(2), **epoll_wait**(2), **poll**(2), **epoll**(7)

COLOPHON

This page is part of release 3.44 of the Linux *man-pages* project. A description of the project, and information about reporting bugs, can be found at http://www.kernel.org/doc/man-pages/.